



General

Product Type	Constant Current Driver
Length (mm)	167
Width (mm)	39
Height (mm)	30
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	175

Electronics

Input Domain	AC
Input Voltage	220 ~ 240V AC
Output Voltage	10 ~ 54V DC
Output Current (mA) max/output	200~1200
Output Power Range (W)	2~36
Power Factor at Full Load	+0.95 @ 230VAC
Power Supply	Internal
LED Outputs	1
Input Frequency	50 ~ 60Hz
Inrush Current	6.31A @ 230VAC

Lighting

Color Range	Single Color
-------------	--------------

Control

Output Signal	PWM-CC
Control	DALI
Dimming Range	0~100%
Number of Channels	1

Protection

Protection Class	II
------------------	----

Environmental

Storage Temperature	-40 ~ +80 °C
Operating Temperature	-30 ~ +50 °C
Ingress Protection	IP20

CE IP20

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

LED Intelligent Driver

2~36W 200~1200mA 10~54Vdc

- Dimming interface: DALI, Push DIM
- PWM digital dimming, no alter LED color rendering index.
- Dimming range: 0~100%, LED start at 0.1% possible.
- Support lamp current state and fault feedback function.
- DALI dimming curve can be either linear or logarithmic.
- Non-load output voltage 0V to prevent damages to LED caused by poor contact.
- Multi-current & wide voltage, suitable for different power LED.
- Short circuit / Over-heat / Over load / Non-load protection.
- Class 2 power supply. Full protective plastic housing.
- DALI bus standard: IEC62386-101, 102, 207.
- Compliant with Safety Extra Low Voltage standard.
- Suitable for internal lights application for I / II / III.




Dimmable:
0.1%~100%

TUV Certificate No. B 17 06 01119 001
BIS Certificate No. R-41072265
CB Certificate No. SG PSB-LE-00609
RCM Equipment registration No: E2017013627 Ref: ESV170365
ENEC Certificate No. U6 17 07 01119 004
CE EMC Certificate No. B5T1702498520001Y-1EC-1
LVD Certificate No. B5T1709992470001Y-1SC-2
CCC Certificate No. 2017011002993756



R-41072265



Main Characteristics

Dimming Interface:	DALI (IEC62386), Push Dim						
Input Voltage Range:	220-240Vac $\pm 10\%$						
Frequency:	50/60Hz						
Input Current:	<0.3A						
Power Factor:	PF>0.95/230Vac, at full load						
THD:	$\leq 20\%$ at 230Vac, at full load						
Efficiency:	>87%						
Inrush Current(typ.):	Cold start 6.31A at 230Vac (twidth=58.4 μ s measured at 50% Ipeak)						
Control Surge Capability:	L-N: 1kV						
Leakage Current:	<0.5mA/230Vac						
Operating Voltage:	10~54Vdc						
Output Power Range:	2W~36W						
Output Current :	200mA	350mA	500mA	600mA	700mA	900mA	1050mA
Output Voltage :	10~54V	10~54V	10~54V	10~54V	10~52V	10~40V	10~35V
Output Power :	2W-10.8W	3.5W-18.9W	5W-27W	6W-32.4W	7W-36.4W	9W-36W	10.5W-36.75W

Current Accuracy:	$\pm 3\%$
Max Output Voltage:	58Vdc
Non-load Output Voltage:	0Vdc
PWM Frequency:	≤ 4 KHz
Dimming Range:	0~100%, LED start at 0.1% possible.
Working Temperature:	ta: -30°C ~ 50°C tc: 90°C
Working Humidity:	20 ~ 95%RH, non-condensing
Storage Temp., Humidity:	-40 ~ 80°C, 10~95%RH
Temp. Coefficient:	$\pm 0.03\%/^{\circ}\text{C}$ (0~50°C)
Vibration:	10~500Hz, 2G 12min./1cycle, period for 72min. each along X, Y, Z axes

Protection

Over-heat Protection:	Shut down the output when PCB temp. $\geq 110^{\circ}\text{C}$, auto recovers when temp. back to normal.
Over Load Protection:	Shut down the output when rated power $\geq 102\%$ ~125%, auto recovers when the load is reduced.
Short Circuit Protection:	Shut down automatically if short circuit occurs, auto recovers after faulty condition is removed.
Non-load Protection:	Shut down the output if no load, auto recovers when load back to normal.


Safety & EMC


Withstand Voltage:	I/P-O/P: 3750Vac
Isolation Resistance:	I/P-O/P: 100M Ω /500VDC/25°C/70%RH
Safety Standards:	IEC/EN61347-1, IEC/EN61347-2-13
EMC Emission:	EN55015, EN61000-3-2 Class C, IEC61000-3-3
EMC Immunity:	EN61000-4-2, 3, 4, 5, 6, 8, 11 EN61547

Others

Dimension:	167 $\times$ 39 $\times$ 30mm(L $\times$ W $\times$ H)
Packing:	168 $\times$ 41 $\times$ 32mm(L $\times$ W $\times$ H)
Weight[G.W.]:	160g $\pm$ 10g

Dimensions





Push Dimming



Reset Switch

- On/off control: Short press.
- Stepless dimming: Long press.
- With every other long press, the light level goes to the opposite direction.
- Dimming memory: Brightness will be the same as previously adjusted when turning off and on again.

LED Current Selection

Quick options: DIP switch for 8 optional currents' quick selection[see the table below].

200mA	350mA	500mA	600mA	700mA	900mA	1050mA	1200mA	ON	OFF
10-54V	10-54V	10-54V	10-54V	10-52V	10-40V	10-35V	10-30V		

* After current setting by DIP switch, power off and then power on to make the new current effective.

* E.g. LED 3.2V/pcs: 10-54V can power 3-16pcs LEDs in series, 10-30V can power 3-9pcs LEDs, the max quantity of LEDs in series will be subject to the actual voltage of LED.

Relationship Diagrams

