Beam F120



General	
Width (mm)	404
Height (mm)	272
Depth (mm)	123.5
Cover	Tempered Glass
Housing Material	Aluminum - ACD12
Mounting	Surface mounted
Connector	M16 - 5 pin
Electronics	
Input Voltage	220 ~ 240V AC
Power Consumption (W)	120
Power Supply	Internal
Lighting	
Emission	Direct
LED Type	Single Color Leds
LEDs per Spot	60
Colour Rendering Index (CRI)	80
Luminous Flux	7000lm (RGBW3000K 45)
Control	
Control	DMX
Control Units	Single pixel
Environmental	
Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Impact Protection	IK07
Ingress Protection	IP67



CE ROHS IP67 3 year warranty


Disclaimer


Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.


181



OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com







+31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com