

#### General

Constant Voltage Driver
104
58
9
White
Plastic
Surface mounted
42
5mm
2.5mm2

### **Electronics**

Input Domain	DC
Input Voltage	12 ~ 24V DC
Output Voltage	12 ~ 24 V DC
Output Current (mA) max/output	5000
Output Current Max. (A)	5
Output Power (W)	100W @ 5V, 240W @ 12V, 480W @ 24V,
Power Supply	N/A
LED Outputs	4

## Lighting

Color Range RG	BW
----------------	----

## Control

Output Signal	RF, PWM-CV
Control	Manual
Remote Distance	40m
Zones	1
Number of Channels	4
Functions	programmable

## **Protection**

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes

### **Environmental**

Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP20
Battery	1x CR2032

CE FC IP20 5 year warranty

# Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

181

oneeighty one.com