



General

Product Type	Constant Voltage Driver
Length (mm)	104
Width (mm)	58
Height (mm)	9
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	42
Wire Strip Length	5mm
Wire Type	2.5mm2

Electronics

Input Domain	DC
Input Voltage	12 ~ 24V DC
Output Voltage	12 ~ 24 V DC
Output Current (mA) max/output	3000
Output Current Max. (A)	9
Output Power (W)	108W @ 12V, 216W @ 24V
Power Supply	N/A
LED Outputs	3

Lighting

Color Range	Tunable White
-------------	---------------

Control

Output Signal	RF, PWM-CV
Control	Manual
Remote Distance	40m
Zones	1
Number of Channels	2
Functions	programmable

Protection

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes

Environmental

Operating Temperature	-20 ~ +55 °C
Ingress Protection	IP20
Battery	1x CR2032

CE FCC IP20 5year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

