

#### General

Product Type	Controller
Length (mm)	86
Width (mm)	86
Height (mm)	36
Housing Color	White
Housing Material	PC
Mounting	Built-in
Weight (g)	225

### **Electronics**

Input Domain	AC
Input Voltage	100 ~ 240V AC
Power Supply	Internal
LED Outputs	4

# Lighting

Color Range RGE	3W
-----------------	----

#### Control

Output Signal	DMX, RF
Control	DMX, Radio Frequency
Zones	4
Number of Channels	4
Functions	programmable

### Environmental

Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP20

CE IP20 5 year warranty

# Disclaimer


Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.



oneeighty one.com

LTECH

# **EX8** Touch Panel (RGBW)





Manual www.ltech-led.com

# Technical Specs EX8 RGBW Touch Panel (4 zones)

100~240Vac

-30°C~55°C

5~24Vdc

Max Output Power: 60W/144W/288W(5V/12V/24V)

5~24Vdc

RF 2.4GHz, DMX512

3A × 4CH Max. 12A

5A × 4CH Max. 20A

100W/240W/480W(5V/12V/24V)

CC 350/700/1050mA×4CH

1.05W~48.3W×4CH Max 193.2W



Package Size:

Weight(G.W.):



LTECH

L86×W86×H36(mm)

L113×W112×H50(mm)


L125×W33×H20(mm)


L175×W44×H30(mm)


L178×W48×H33(mm)



EX8








#### **Key Functions:**




\* When the touch panel is off, Long press 😃 to turn on/off the buzzer When the touch panel is on ,Long press  $\stackrel{\mbox{\scriptsize $\bullet$}}{\bigcirc}$  to match code.

#### Terminals:





LTECH



LTECH



Output Voltage:

Output Current:

Wireless Signal:

Output Power:

Input Voltage:

Output Signal:

Working Temp.:

Input Voltage:

Current Load:

Input Voltage:

Current Load:

F4-3A CV Receiver

F4-5A CV Receiver

Wireless Signal: 2.4GHz

Wireless Signal: 2.4GHz

Note: Receiver is sold separately.

Input Voltage: 12~48Vdc

2.4GHz

Working Temp.: -30°C~55°C

Package Size:

Weight(G.W.):

Working Temp.: -30°C~55°C

Working Temp.: -30°C~55°C

Weight(G.W.): 60g

Package Size: L127×W35×H24(mm)

150g

L175×W44×H30(mm)


Package Size: L178×W48×H33(mm)

Weight(G.W.): 165q

FC ( FROHS (warranty) 5 years) 150901:2008







LTECH

Match code:

DMX Wiring:

RF Wireless Wiring:

LTECH

\_\_\_\_\_\_

Multi-control Wiring:

LTECH

\_\_\_\_\_\_

Match/Clear Code between Touch Panel & Receiver

Match/Clear Code between Touch Panels:

Match code:

LTECH