

### General

Length (mm)	155
Diameter (mm)	120
Built-in Diameter (mm)	104
Cover	8mm step tempered glass, Stainless steel (SUS316),
Housing Color	Silver
Housing Material	Aluminum / ABS
Diameter Mounting Sleeve (mm)	104
Length Mounting Sleeve (mm)	155
Cut-out (mm)	105
Cable Color	Black
Cable Length (cm)	50 cm
Cable Type	H05RN-F3xG0.75

## **Electronics**

Input Domain	AC
Input Voltage	220 ~ 240V AC
Power Consumption (W)	17
Power Supply	Internal
Luminous Efficacy	75 lm/W

# Lighting

Emission	Direct
Optics (°)	13
Chip Brand	CREE
LED Type	COB
LED Quantity	1
Color Range	White
Color Temperature (Kelvin)	3000 K
Colour Rendering Index (CRI)	82
Luminous Flux	1320 lm
Light Distributor	Other
Light Sharing	Symmetric

#### Control

Number of Channels

# Environmental

Operating Temperature	-20 ~ +40 °C
Impact Protection	IKO8
Ingress Protection	IP67



CE ROHS IP67 2 year warranty

#### Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

oneeighty one.com