



General

Length (mm)	94
Diameter (mm)	150
Built-in Diameter (mm)	150
Cover	8mm step tempered glass, Stainless steel (SUS316),
Housing Color	Silver
Housing Material	Aluminum / PC
Diameter Mounting Sleeve (mm)	150
Length Mounting Sleeve (mm)	113
Cut-out (mm)	151
Cable Length (cm)	50 cm
Core	1 mm2
Number of Cores	4

Electronics

Input Domain	DC
Input Voltage	24 V DC
Power Consumption (W)	18
Power Supply	External
Luminous Efficacy	56 lm/W

Lighting

Emission	Direct
Optics (°)	40
LED Type	3in1
LED Quantity	6
Color Range	RGB
Luminous Flux	1020 lm
Light Distributor	Other
Light Sharing	Symmetric

Control

Number of Channels	3
--------------------	---

Environmental

Operating Temperature	-20 ~ +40 °C
Impact Protection	IK08
Ingress Protection	IP67



IP67 2<sup>year</sup> warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

