

Linear LED Wallwasher



General

Length (mm)	1000
Width (mm)	37
Height (mm)	53
Cover	Aluminum + Lens Optics
Housing Material	Aluminum – AA 6063
Mounting	Surface mounted
Weight (g)	1300
Cable Length (cm)	50 cm
Connector	M16 – 5 pin

Electronics

Input Voltage	24 V DC
Power Consumption (W)	36
Power Supply	External
Energy Class	A

Lighting

Emission	Direct
Optics (°)	10x60 (optional: 15, 25, 45)
LED Quantity	48
LED Spacing (mm)	21
Color Range	RGBW, White
Color Temperature (Kelvin)	2700 K, 5500 K
Colour Rendering Index (CRI)	80
Luminous Flux	1980 lm (RGBW), 2700 lm (2700K), 3000 lm (5500K),

Control

Control	DMX
Control Units	Single pixel

Environmental

Storage Temperature	-30 ~ +60 °C
Operating Temperature	-30 ~ +50 °C
Impact Protection	IK07
Ingress Protection	IP67
Enclosure	IEC 60529



IP67 3 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

