



General

Dimensions (mm)	1000 x 52 x 55
Cover	Tempered Glass
Housing Color	Grey
Housing Material	Aluminum - AA 6063
Weight (g)	3685
Cable Length (cm)	15 cm
Connector	M16 - 5 pin

Electronics

Input Voltage	24 V DC
Power Supply	External
Power Consumption (W)	54
Luminous Efficacy	49 lm/W
Energy Class	A

Lighting

Emission	Direct
Optics (°)	10x60 (optional: 12, 12x49)
LED Type	Cree SMD3535
Color Range	RGB
LED Quantity	36
LED Spacing (mm)	28
Luminous Flux	2640 lm (RGB)
Colour Rendering Index (CRI)	-
Color Temperature (Kelvin)	

Control

Control	DMX
Control Units	Single pixel
Number of Channels	3

Environmental

Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Impact Protection	IK07
Ingress Protection	IP67
Enclosure	IEC 60529



IP67 3^{year} warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

