

# Gobo projector LED



## General

|               |        |
|---------------|--------|
| Length (mm)   | 305 mm |
| Diameter (mm) | 72     |

## Electronics

|                       |               |
|-----------------------|---------------|
| Input Voltage         | 220 ~ 240V AC |
| Power Consumption (W) | 20            |
| Powerfactor           | 0.9           |
| Luminous Efficacy     | 88 lm/W       |
| THD (at full load)    | 15%           |
| Input Frequency       | 50 ~ 60Hz     |

## Lighting

|                  |            |
|------------------|------------|
| Emission         | Direct     |
| Lifespan (hours) | 30000      |
| Luminous Flux    | 1800 lm    |
| Light Color      | Cold White |

## Control

|            |                      |
|------------|----------------------|
| Connection | 3-Phase rail adapter |
|------------|----------------------|

## Environmental

|                    |      |
|--------------------|------|
| Ingress Protection | IP20 |
|--------------------|------|



IP20

### Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

