



General

Product Type	Constant Current Driver, Wireless,
Length (mm)	167
Width (mm)	41
Height (mm)	32
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	160

Electronics

Input Domain	AC
Input Voltage	100 ~ 240V AC
Input Current max (A)	0.13A @ 230V AC
Output Voltage	9 ~ 54V DC
Output Current (mA) max/output	250~1000
Power Consumption (W)	20
Output Power Range (W)	2.25~20
Power Factor at Full Load	+0.90 @ 230VAC
Power Supply	Internal
LED Outputs	2
Anti Surge	L-N: 2kV
Efficiency	83%
Leakage current max. (mA)	0.24
Input Frequency	50 ~ 60Hz
Inrush Current	10A @ 230VAC

Lighting

Color Range	Tunable White
-------------	---------------

Control

Output Signal	PWM-CC
Control	Bluetooth
Dimming Range	0~100%, 0.1% dimming depth.
Number of Channels	2

Protection

Protection Class	II
------------------	----

Environmental

Storage Temperature	-40 ~ +80 °C
Operating Temperature	-20 ~ +50 °C
Fire-retardant	V-0
Ingress Protection	IP20
Safety Standards	NEN-EN-IEC 61347-1, NEN-EN-IEC 61347-2-13,

CE

RoHS

COMPLIANT

IP20

5 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.