



General

Width (mm)	404
Height (mm)	272
Depth (mm)	123.5
Cover	Tempered Glass
Housing Material	Aluminum - ACD12
Mounting	Surface mounted
Connector	M16 - 5 pin

Electronics

Input Voltage	220 ~ 240V AC
Power Consumption (W)	120
Power Supply	Internal

Lighting

Emission	Direct
LED Type	Single Color Leds
LEDs per Spot	60
Colour Rendering Index (CRI)	80
Luminous Flux	7000lm (RGBW3000K 45)
Color Range	RGBW
Optics (°)	25
Color Temperature (Kelvin)	3000 K

Control

Control	DMX
Control Units	Single pixel
Number of Channels	4

Environmental

Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Impact Protection	IK07
Ingress Protection	IP67

CE

RoHS

COMPLIANT

IP67 3 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.