Beam F54 Neutral White 4000K - 24V - 60°

3427319



General

Width (mm)	203
Height (mm)	230
Diameter (mm)	180
Cover	Tempered Glass
Housing Color	Grey
Housing Material	Aluminum - ACD12
Mounting	Surface mounted
Connector	M16 - 5 pin

Electronics

Power Consumption (W)	54
Input Voltage	24 V DC
Power Supply	External (not included)

Lighting

Emission	Direct
LED Quantity	24
LEDs per Spot	24
Colour Rendering Index (CRI)	80
Luminous Flux	3180lm (RGBW3000K)
Color Range	White
Optics (°)	60
Color Temperature (Kelvin)	4000 K

Control

Control	DMX
Control Units	Single pixel
Number of Channels	3

Environmental

Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Impact Protection	IK07
Ingress Protection	IP67

CE RoHS COMPLIANT IP67 3 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam
+31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com

©2024

oneeighty one.com

Paper size: A4