



General

| | |
|------------------|----------------------------|
| Width (mm) | 30 |
| Height (mm) | 48 |
| Housing Color | Grey |
| Housing Material | Aluminum |
| Mounting | mounting brackets included |
| Cable Type | H05RN-F3xG1 |
| Connector | M16 - 3 pin |
| Length (mm) | 1500 |

Electronics

| | |
|-----------------------|---------|
| Input Voltage | 48 V DC |
| Power Consumption (W) | 22 |

Lighting

| | |
|------------------------------|----------------|
| Optics (°) | 160 |
| LED Spacing (mm) | 15 |
| Pixel Pitch | 75 mm |
| Luminous Flux | 185 lm/m (RGB) |
| Color Range | RGBW |
| LED Quantity | 100 |
| LED Type | 4in1 |
| Colour Rendering Index (CRI) | 80 |
| Color Temperature (Kelvin) | 4000 K |

Control

| | |
|--------------------|---------|
| Control | SPI |
| Compatible ICs | UCS8904 |
| Number of Channels | 80 |
| Pixels per fixture | 20 |

Environmental

| | |
|-----------------------|--------------|
| Storage Temperature | -30 ~ +65 °C |
| Operating Temperature | -20 ~ +55 °C |
| Impact Protection | IK07 |
| Ingress Protection | IP68 |

CE IP68

2^{year}
warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.