Linear G36 RGBW3000K - 24V - 12*49°

3423626



General	
Length (mm)	1000
Width (mm)	42
Height (mm)	70
Cover	Tempered Glass
Housing Color	Grey
Housing Material	Aluminum - AA 6063
Connector	M16 – 5 pin
Electronics	
Input Voltage	24 V DC
Power Consumption (W)	36
Power Supply	External (not included)
Lighting	
Emission	Direct
LED Quantity	36
LED Spacing (mm)	27.7
Colour Rendering Index (CRI)	80
Luminous Flux	1350 lm/m (RGBW)
Color Range	RGBW
Optics (°)	12x49
Color Temperature (Kelvin)	3000 K
Control	
Control	DMX
Control Units	Single pixel
Number of Channels	4
Environmental	
Storage Temperature	-40 ~ +70 °C

Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP67





Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice. 181

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com



oneeighty

one.com