

Digital LED Cable 2x1 + 2x0.14



General

| | |
|---------------------|--|
| Length (m) | 100 |
| Diameter (mm) | 6.1 |
| Housing Material | Special halogenfree compound (TM7), |
| Conductor Stranding | 0.14 cores twisted to a pair, covered with polyester tape, |
| Cable Color | Black |
| Core | 2x1/2x0.14mm2 bare copperwires acc. IEC 60228, |
| Core Identification | 0.14mm2 red/white 1.00mm2 red/white, |
| Core Isolation | Special halogenfree compound (TI6), |

Electronics

| | |
|--------------------------|---|
| Characteristic Impedance | (1x2x0.14mm ²) : ? 110 ohm |
| Conductor Resistance | 0.14mm ² : max. 135 ohm/km - 1mm ² : max. 19.5 ohm/km, |
| Operating Voltage (V) | Max 50V |

Environmental

| | |
|-----------------------|--------------|
| Storage Temperature | -30 ~ +70 °C |
| Operating Temperature | -10 ~ +70 °C |
| UV Constant | yes |
| Halogen Free | yes |



Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

