



General

|                       |         |
|-----------------------|---------|
| Length (mm)           | 5000    |
| Width (mm)            | 8       |
| Height (mm)           | 2       |
| Housing Color         | White   |
| Housing Material      | Copper  |
| Mounting              | 3M tape |
| Weight (g)            | 85      |
| Cutting Interval (mm) | 50      |
| Cable Length (cm)     | 15 cm   |

Electronics

|                         |          |
|-------------------------|----------|
| Input Voltage           | 24 V DC  |
| Power Supply            | N/A      |
| Power Consumption (W/m) | 19.2     |
| Luminous Efficacy       | 120 lm/W |

Lighting

|                              |  |
|------------------------------|--|
| Emission                     | Direct   |
| Optics (°)                   | 120  |
| LED Type                     | SMD3040  |
| LED Quantity /m              | 160  |
| LED Spacing (mm)             | 6.25   |
| Color Range                  | White  |
| Color Temperature (Kelvin)   | 4000 K   |
| Colour Rendering Index (CRI) | 95   |
| SDCM                         | 3  |
| TM-21 Projection             | L70 @ 85 °C (LM80-08),<br>Reported 36000,<br>Calculated 60000, |
| Luminous Flux                | 2110 lm/m  |

Control

|                    |              |
|--------------------|--------------|
| Control            | PWM          |
| Control Units      | Single pixel |
| Number of Channels | 1            |

Environmental

|                       |  |
|-----------------------|--|
| Storage Temperature   | -40 ~ +80 °C                               |
| Operating Temperature | -25 ~ +60 °C                               |
| Ingress Protection    | IP20                                       |
| Safety Standards      | EN 62031,<br>IEC 62471,<br>EN60598-1:2015, |



IP20 5 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.



oneeighty  
one.com