Linear G24 Tunable White 3000~6000K - 24V - 10*25° 3422124

General

Length (mm)	1000
Width (mm)	38
Height (mm)	46
Cover	Tempered Glass
Housing Color	Grey
Housing Material	Aluminum - AA 6063
Connector	M16 - 5 pin

Electronics

Input Voltage	24 V DC
Power Consumption (W)	24
Power Supply	External (not included)

Lighting

Emission	Direct
Colour Rendering Index (CRI)	80
Luminous Flux	1025 lm (RGBW)
Color Range	Tunable White
LED Quantity	36
Optics (°)	10x25
LED Spacing (mm)	27.7
Color Temperature (Kelvin)	3000~6000K

Control

Control	DMX
Control Units	Single pixel
Number of Channels	3

Environmental

Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP67

CE RoHS COMPLIANT IP67 3 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam
+31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com

©2024

oneeighty one.com

Paper size: A4