Linear G54 Warm White 3000K - 24V - 10*25°

3421521

General

Length (mm)	1000
Width (mm)	55
Height (mm)	80.5
Cover	Tempered Glass
Housing Color	Grey
Housing Material	Aluminum - AA 6063
Connector	M16 - 5 pin
Electronics	
Power Consumption (W)	54
Input Voltage	24 V DC
Power Supply	External (not included)
Lighting	
Emission	Direct
Colour Rendering Index (CRI)	80
Color Range	White
Optics (°)	10x25
Luminous Flux	3875 lm/m
Color Temperature (Kelvin)	3000 K
Control	
Control	DMX
Control Units	Single pixel
Number of Channels	3
Environmental	
Storage Temperature	-40 ~ +70 °C
Operating Temperature	–30 ~ +55 °C
Ingress Protection	IP67



Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

181

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com



oneeighty

one.com