Beam F36 RGBW3000K - 24V - 45°



General

203
230
180
Tempered Glass
Grey
Aluminum - ACD12
Surface mounted
M16 – 5 pin

36

Electronics

Power Consumption (W)

Lighting

Emission	Direct
LED Quantity	24
LEDs per Spot	18
Colour Rendering Index (CRI)	80
Luminous Flux	1850lm (RGBW3000K)
Color Range	RGBW
Optics (°)	45
Color Temperature (Kelvin)	3000 K

Control

Control	DMX
Control Units	Single pixel

Environmental

Storage Temperature	-40 ~ +70 °C
Operating Temperature	-30 ~ +55 °C
Impact Protection	IK07
Ingress Protection	IP67



CE ROHS IP67 3 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

18

©2024



3427202

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com