Beam F36 Warm White 3000K - 24V - 45°



General Width (mm) 203 Height (mm) 230 180 Diameter (mm) Tempered Glass Cover Housing Color Grey Aluminum - ACD12 Housing Material Mounting Surface mounted Connector M16 - 5 pin Electronics Power Consumption (W) 36 Lighting Emission Direct LED Quantity 24 LEDs per Spot 18 Colour Rendering Index (CRI) 80 Luminous Flux 1850lm (RGBW3000K) Color Range White Optics (°) 45 3000 K Color Temperature (Kelvin) Control Control DMX Control Units Single pixel Environmental Storage Temperature -40 ~ +70 °C **Operating Temperature** -30 ~ +55 °C Impact Protection IK07 **Ingress Protection** IP67

3427203

CE

Rohs

IP67 3^{year}

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

 \mathbf{R}

©2024

oneeighty one.com

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com