Beam F36 Neutral White 4000K - 24V - 8°



203

General Width (mm) 3427224

	200
Height (mm)	230
Diameter (mm)	180
Cover	Tempered Glass
Housing Color	Grey
Housing Material	Aluminum - ACD12
Mounting	Surface mounted
Connector	M16 - 5 pin
Electronics	
Power Consumption (W)	36
Lighting	
Emission	Direct
LED Quantity	24
LEDs per Spot	18
Colour Rendering Index (CRI)	80
Luminous Flux	1850lm (RGBW3000K)
Color Range	White
Optics (°)	8
Color Temperature (Kelvin)	4000 K
Control	
Control	DMX
Control Units	Single pixel
Environmental	
Storage Temperature	-40 ~ +70 °C

-30 ~ +55 °C

IK07

IP67



CE

ROMELANT IP67 3 year warranty

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice. 181

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com **Operating Temperature**

Impact Protection

Ingress Protection

Paper size: A4

oneeighty

one.com