LED Strip HO 3000K

3117301



General

General	
Length (mm)	5000
Width (mm)	10
Height (mm)	2
Housing Color	White
Housing Material	Copper
Mounting	3M tape
Weight (g)	85
Cutting Interval (mm)	50
Cable Length (cm)	15 cm
Electronics	
Input Voltage	24 V DC
Power Consumption (W/m)	14.4
Luminous Efficacy	138 lm/W
Lighting	
Emission	Direct
Optics (°)	120
LED Type	SMD2835
LED Quantity /m	160
LED Spacing (mm)	6.25
Color Range	White
Color Temperature (Kelvin)	3000 K
Colour Rendering Index (CRI)	? 90
Luminous Flux	1990 lm/m
	L70 @ 85 °C (LM80-08), Reported 36000, Calculated 60000,
Control	
Control	PWM
Control Units	Single pixel
Number of Channels	1
Environmental	
Storage Temperature	-40 ~ +80 °C
Operating Temperature	-25 ~ +60 °C
Ingress Protection	IP20
Safety Standards	EN 62031, IEC 62471, EN60598-1:2015,

CE

Disclaimer





Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice. 18

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com

Paper size: A4

oneeighty

one.com